



PVC VINYL SHEETING

For pricing or additional information, please contact us at 1-800-334-0541.

PVC VINYL SHEETING IS A NON-REINFORCED HOMOGENEOUS POLYVINYL CHLORIDE MATERIAL THAT HAS BEEN REDUCED TO A THERMOPLASTIC STATE AND CAREFULLY CALENDERED INTO A CONTINUOUS SHEET. PVC VINYL SHEETING WILL NOT BE PHYSICALLY DEFORMED WHEN STRETCHED AT ROOM TEMPERATURE AND WILL SHOW NO CRACKING OR FLAKING WHEN BENT THROUGH 180 DEGREES OVER A 1/32" MANDREL AT -20 DEGREES F. THIS MATERIAL IS SUITABLY STABILIZED TO RESIST EXPOSURE WITHOUT PHYSICAL DETERIORATION WHEN TESTED IN ACCORDANCE WITH ASTM STANDARDS D-822 FOR A PERIOD OF NOT LESS THAN 400 HOURS.

ADVANTAGES

- **HIGH MECHANICAL STRENGTH, RESISTANT TO TEAR, PUNCTURE OR ABRASION**
- **RESISTANT TO ACIDS, ALKALIES, CAUSTICS, FUNGUS AND MILDEW**
- **REMAINS FLEXIBLE AT LOW TEMPERATURES AND NOT AFFECTED BY EXTREME TEMPERATURE CHANGES**
- **WILL NOT ROT, STAIN, OR BLEED**

USES

MEMBRANE WATERPROOFING FOR FOUNDATION WALLS, SLABS, ON GRADE AND ABOVE GRADE CONCRETE DECKS-THRU-WALL FLASHING IN BOTH MASONRY AND FRAME CONSTRUCTION-TERMITE SHIELD-SHOWER PANS-SPANDREL BEAM.

PHYSICAL PROPERTIES (FOR 20 MIL)

- **ASTM D 412-61T TENSILE STRENGTH OVER 2000 PSI**
- **ELONGATION 250+ %**
- **TEAR RESISTANCE 250 LBS. PER SQUARE INCH**

| THICKNESS | DIMENSIONS | |
|------------------|-------------------|--------------|
| 10 MIL | 6" - 48" X 150' | 0.875 x inch |
| 20 MIL | 6" - 48" X 150' | 1.50 x inch |